# AIRPORT EQUIPMENT FAA WIND DIRECTION INDICATOR

3 OR 6 METERS



# 01. DESCRIPTION

Our **FAA WDI** is compliant to the FAA rules. It is manufactured in galvanized steel with an orange paint and is available in 3 or 6 meters. The 3M WDI is tiltable at the base of the mast and the 6M WDI is tiltable in the middle of the mast.

3 diameters of preformed wind vane are proposed together with the suitable windsocks. The wind vane support is equipped with two auto-lubricated teflon rings to allow its rotation. This system is very resistant to wear phenomena, and doesn't require any maintenance, therefore offering an exceptional life time.

Various options are available such as the windsock lighting (internal or external) and the topmast Obstacle Light. These options can operate under different power supplies: 24-48V, 230V, Solar but also in 6,6 A.

# 02. MODELS

REFERENCE	3 METERS	6 METERS	WIND VANE DIAMETER	
REFERENCE	3 WETERS		СМ	INCHES
FAA3-BG30	×		30	12'
FAA3-BG45	X		45	18'
FAA3-BG60	X		60	24'
FAA6-BG45		X	45	18'
FAA6-BG60		X	60	24'
FAA6-BG90		X	90	36'



Hoist (in option)



External Lighting + Obstacle Light



Solar power supply









SCOPE OF APPLICATIONS



# **03. CHARACTERISTICS**

MECHANICAL				
Height	3 or 6 meters			
Tiltable part location	Base (3 meters WDI) or Middle (6 meters WDI)			
Protection	Galvanized steel			
Paint	Orange			
Mounting	Anchorage Block (Included)			
Anchorage Block	600 x 600 x 800 mm			
Preformed wind vane	30 / 60 / 90 cm			
Braces	No			
ENVIRONMENTAL				
Humidity	100%			
Frost	-60°C			
Wind speed	160 Km/h			
CERTIFICATIONS				
FAA	Compliant			
Quality	ISO 9001; 2008			
Warranty	1 year			
ELECTRICAL				
Power supply	6.6A / 230V / 2V (Solar)			
Operating temperature	-55°C to +55°C			
Consumption	3 Watts (obstacle light)			
Gonoumpuon	30 Watts (external light)			
Protection Class	IP66			
OPTIONS				
Reinforced mast	•			
Obstacle Light	<b>©</b>			
External lighting by 4 Leds Floodlights (230V or 6.6A) Consumption < 4 x 5.2 W	•			
Paint	Red & White or Yellow			
Frangibility of the mast	<b>②</b>			
Solar power supply	•			
Stainless steel / Aluminum / Fiber Glass manufacture	<b>©</b>			

# DIMENSIONS FAA WDI of 3 meters Ø48.3x3 FAA WDI of 6 meters

### **AVAILABLE ACCESSORIES FOR INSTALLATION**

- Windsock
- Solar power supply









